

INDUSTRIAL UV HYBRID PRINTER WITH RICOH PRINT HEAD



- ☑ 2.0m printing width
- ☑ 5PL/7PL variable ink droplet, high resolution printing
- ☑ All steel print head with a longer life time and it is corrosion resistant
- ☑ Imported silent linear guide railway, stable operation
- ☑ Intelligent ink alarm system
- ☑ Automatic height detecting and positioning system
- ☑ Independent control of Color and White negative pressure systems




理光G6工业喷头
Ricoh Gen6
Printhead



理光G5工业喷头
Ricoh Gen5
printhead



LED水冷固化灯
LED UV water-
cooling Lamp



双金属压辊
Bimetal pressure
roller

Technical Parameters

Model	CY-RF2000		Feeding System	Inflatable Rollers + Automatic Rotary Motor
Print Head	Ricoh Gen5 / Gen6		Taking up System	Inflatable Rollers + Automatic Rotary Motor
Print Head QTY	2~12 pcs		Operation System	Microsoft Windows7(x64) /Windows10 (X64)
Ink Droplet Size	5PL / 7PL		Rip Software	Photo Print
Printing Speed 3 x KC MY	Gen5	Gen6	Color Control	International ICC standard with adjusting function for profiles and density
	draft mode: 60m ² /h	draft mode: 78m ² /h	Image Format	TIFF, JPEG, CMX, AI, PSD, PS, PDF, EPS
	Production mode: 40m ² /h	Production mode: 52m ² /h	Printing Materials	ceiling film, banner, vinyl, reflective film, wall cloth, canvas, leather, carpet, PET, etc
	Quality mode: 30m ² /h	Quality mode: 39m ² /h		ceramic, glass, PVC board, acrylic, bamboo fibreboard, steel, aluminum, etc.
Printing colors	C M Y K Lc Lm W V		Data Interface	High speed USB3.0 / LAN Cable
Printing Width	2.0m		Power Supply	Single Phase AC 220v (±5%) , 50/60Hz, 18A, earth line is a must
Media Thickness	Flexible Media: 0~10mm; Rigid Media: 0~60mm		Working Temperature	15℃~30℃
Material Handling	Flexible and rigid materials		Working Humidity	40%~70% Relative humidity
Ink	Imported UV Ink		Dimension	4,20m*1,00m*1,65m
Curing System	LED UV water-cooling		Weight	980kg

应用案例 APPLICATION CASE



亚克力板
acrylic



刀刮布
Knife scraper



竹木纤维板
Bamboo fiberboard



车身贴
sticker



雪弗板
PVC