


2513 UV FLATBED PRINTER

Machine Instruction


- ▶ Ricoh Gen5 / Gen6 Print Head
- ▶ Automatic height detection system
- ▶ Anti-collision system
- ▶ Intelligent constant temperature ink system
- ▶ LED UV water cooling system, higher performance power energy consumption
- ▶ Intelligent ink level alarm system



Industry Application



Acrylic backlit



wallpanels



glass splashbacks



Marble



Gift Box

Machine Parameters

MODEL	2513 UV FLATBED PRINTER	
PRINthead	Ricoh GEN5/GEN6 Industrial Grayscale Print Head	
PRINT HEAD NUMBER	2-8ph	
PRINT MODE	4C/6C/4C+W/6C+W/4C+W+V/6C+W+V	
PRINT WIDTH	2500mm x 1300mm/8*4ft	
PRINT SPEED (sqm/h)	4PASS	18sqm/h
	6PASS	15sqm/h
	8PASS	12sqm/h
Print Resolution	4 PASS: 720x600 DPI: 6 PASS: 720X900 DPI: 8 PASS: 720*1200 DPI	
Media Type	Glass, Acrylic, Wood, Ceramic, Metal Sheet, PVC Sheet, Plastic, 3C product etc.	
Media Thickness	100mm / Max. 100mm	
Ink Type	UV Ink	
Special Ink	LED Optional White Ink or Varnish	
Curing System	LED Curing System	
File Format	TIFF / JPEG / POSTSCRIPT3 / PDF	
RIP Software	Print factory / Photo print	
Data Connector	USB3.0	
Power	220VAC(*10%), 50/60HZ 220 VAC(*10%) Single Phase, 50/60 HZ	
Power Consumption	3.5 KW	
Machine Size/N.W	4.6 m x 2 m x 1.45m. 1200kgs	
Packing Size/G.W	4.7 m x 2.3 m x 1.65m. 1600kgs	
Environment Requirement	Separated, clean, low dust, well-ventilated environment Working Temperature20°C-28°C Relative humidity: 40%-60%	

ANS Enterprises

2002 G/I, Gali No. - 8, Chuna Mandi, Paharganj,
New Delhi-110055
Mobile : 9811822325
E-mail : salesansentp@gmail.com